



DEMOLITION DERBY

CUMBERLAND COUNTY FAIRGROUNDS | 701 W CUMBERLAND • GREENUP, ILLINOIS

SATURDAY, MAY 29TH, 2021

STOCK COMPACT

1st Place - \$5000 2nd Place - \$2000 3rd Place - \$1000

Consolation Heat Winner - \$1000

Inspection 1:00 - 4:00 PM Start Time: 6 PM

\$50 ENTRY FEE \$40 PASSENGER

15 CARS PER HEAT | TOP 5 CARS OUT OF EACH HEAT WILL ADVANCE TO FEATURE

HEAT PAYOUT: 1st - \$100 2nd - \$75 3rd - \$50

1. 105" Wheelbase or Less.
2. All vehicles must be stock framed and bodied, but motor swaps are allowed no modified engines. NO switching intakes or carburetors. 4- and 6-cylinder engines only. No extra reinforcements may be made to frames or bodies, no welds anywhere but front bumper and doors.
3. All doors are to be fastened shut by #9 wire, chain or weld.
4. Hoods need to be open for inspection. Hoods may be fastened shut in four (4) places total. Two (2) strands of #9 wire per hole, per location. You may wire around frames. Wiring to the front bumper in two (2) places only. Wiring may not be located in front of or behind radiator. No extra bolts in Hoods or Trunks. Trunk lids may be fastened shut using #9 wire or chain in no more than 4 places.
5. Any Factory Car bumpers and mountings are allowed. Weld your bumpers and mounts. No skid plates are allowed. Rear wheel drive cars bumper mounts must be on outside of frame and no direct welding bumper to frame must have mount. 12 in Bumper Shock. Bumper 6" from frame.
6. Front wheel drive cars only may add a 4 by 4 by quarter inch square bumper to the front and back no bumper skin needed. Front Bumper must be 6" from the frame – Rear Bumper no closer than 4" (NEED TO HAVE A SAFETY CHAIN WELDED OR BOLTED TO BUMPER THAT CONNECTS TO FRAME ON BOTH SIDES FOR SAFETY TO KEEP BUMPER FROM FLYING OFF) unless you use #9 wire in hood to bumper.
7. No Distributor protectors or engine cradles. Engine and transmission mounts maybe welded or chained. For safety, a driver's side bar, not to exceed 32" past the bottom rear of front seat and must be used. You may use spreader bars on both sides, but safety cages may only be fastened to sheet metal and may not be attached to the floor or frame of the vehicle with down bars. All cages not to exceed 32" past bottom rear of driver's seat. Dash, rear, and sidebars must be welded in or bolted.
8. Frame seams may not be welded on stock Class and inspection holes must remain open. 3-inch patch may be used on one side of frame, front, and back a total of 4 patches, there must be a bend or rust hole in frame in order to put a 3" plate on one side of frame. No adding anything to the inside of frames, (Concrete, Steel, Wood, etc.) Hump plates for rear frames will not be allowed in compact class.
9. Keep the height of the vehicle reasonable. This will be to judges' discretion. Cars must have bounce to them. You may chain rear ends or wire them in place.
10. Stock rear ends and axles only! Rear ends may be welded.
11. NO Slider Shaft's
12. NO Double Tires – NO Split Rims – NO Wheel Protectors – NO Solid Tires all tires must have air. NO Tires larger than 15" ... or heavier than 6 ply. You may use tractor type tread tires.
13. NO V8 Engines
14. NO All Threads or Bolts in Hood or Trunk
15. NO Built Pointed Bumpers, NO replicant bumpers
16. NEED to have at least 14" x 14" hole in hood in case of fire.
17. NO aftermarket shifters
18. NO aftermarket footfeets
19. You may replace steering columns

No Profanity on Any Cars!

No Exceptions on these Rules...If it is in the rules DO IT (if not DON'T)

**Check All Rules before Coming. General Rules apply to all classes.
Contact Stacey Holsapple @ 217-923-1507 or Scott Justice @ 217-251-6094**