

**Winner - \$1000****Second Place - \$ 300****Third Place - \$200**

1. Battery goes in front floorboard.
2. Gas can in rear floorboard
3. No. 9 wire 2 strands in 4 places on the hood and 4 on the trunk. You may wire around front bumper or rear. 2 - 3/4 all threads allowed in trunk area only may go through frame
4. You may weld all 4 doors.
5. You may add 3/4 all thread for body mounts only
6. May build a front bumper only 4x4 square tubing no bigger than quarter inch, otherwise must be original bumper.
7. You may have a 4x4 mounting bracket 12" long for bumper. Mount may be welded solid to frame on the outside. Bumper must be mounted at least 3" from the front of frame. **(NEED TO HAVE A SAFETY CHAIN WELDED OR BOLTED TO BUMPER THAT CONNECTS TO THE FRAME ON BOTH SIDES FOR SAFETY TO KEEP BUMPER FROM FLYING OFF)**
8. You may weld rear ends. **NO** supports to rear ends or adding leaf springs.
9. You may have an after market shifter and foot feet
10. You may swap engines ...all engines must be stock.
11. Header and Stock Manifolds
12. Cage must be bolted to sheet metal. Side bar no further back than 32" past the bottom rear of front seat and you may have dash and seat bar.
13. Front window bars are allowed.
14. No slider shafts.
15. Gas tank protector no further back than 40" from bottom of front seat must stay in front of rear axle.
16. Lower engine cradle only.
17. **NO** Imperials or Suicide Door Lincoln
18. You can change steering column

**No Exceptions on these Rules...****If it is in the rules DO IT – If not DON'T**

Check All Rules before Coming General Rules apply to all classes

Contact Stacey Holsapple @217-923-1507

Scott Justice @ 217-251-6094 or Dustin McCullough @ 217-251-4614

