

First - \$1000    Second - \$400

Third - \$300

October 5, 2024

Starts at 6 pm

1. NO Hearses, 4x4 vehicles, or Convertibles will be allowed.
2. All vehicles must be stock framed and bodied, but motor swaps are allowed.
3. All doors are to be fastened shut by #9 wire, chained, or welded.
4. Hood may be fastened shut in six (^) places total. Two (2) strands of #9 wire per hole, per location. You may wire around frames. Wiring to the front bumper in tow (2) places only. 2- ¼ all thread one on each side and may go through the frame may be used on either side of the radiator support. Trunk lids may be fastened shut using #9 wire, chain, or weld, you may use 2 all thread 1 on each side ¾ inch, can go through the frame.
5. You may use or reinforce any original car bumper or you may use a replicate car bumper but it must stay within the factory specifications
6. For safety, a driver's side bar, not to exceed 40" past bottom\*\*\*rear of driver's seat. You may use spreader bars on both sides, safety cages may be fastened to frame of the vehicle with straight down bars. All cages not to exceed 40" past bottom rear of driver's seat. Dash, rear, and sidebars must be welded in or bolted.
7. Frame seams may be welded, and inspection holes must remain open. There must be a bend or rusted frame in order to use a use a patch to frame. 6-inch patch may be used on one side of the frame, front, and back a total of 6 patches, 3 on each side. No adding anything to the inside of frames (Concrete, Steel, Wood, Etc.) Hump plates for rear frames will be allowed. 8" down from top of hump both sides of frame.
8. 3/4 ton rear ends may be used no bigger than 8 lug. Can change rear springs no more than 8 leaf springs per side.
9. No tires larger than 16". Rims must be free of wheel weights. No split rims, and no studded tires. Water is allowed. Solid tires allowed
10. **NO** Double Tires

**YOU MAY:**

- 1) Have slider shafts
- 2) Replace steering columns
- 3) Run 3 speed transmission
- 4) Bought shifters are allowed
- 5) Replace foot feeds
- 6) May have Lower Cradle
- 7) May Replace Body Bolts (maybe welded direct to frame.
- 8) No aftermarket ball joints or A-arms
- 9) May have Radiator Protector

**No Exception on these on these No Rear End Protectors Rules...****If it is in the rules DO IT – If not DON'T**

Check All Rules before Coming General Rules apply to all classes

Contact Stacey Holsapple @217-923-1507

or Dustin McCullough @217-251-4614

**DRIVERS MUST BE WITH THE VEHICLE AT CHECK IN**