

## Stock Small Trucks/SUV/Van

1. Battery secured in floorboard and covered.
2. Gas can mounted in bed and covered.
3. Gas tank protector no farther back than 40" from bottom of front seat. May be 6" wider than gas can on each side not full width of truck.
4. Cage to body only= Dash Bar- Front driver and passenger door protectors and seat bar may have a rollover bar one only no kickers bolted to the bed.
5. You may add a 4 x 4 bumper 1/25 inch thick must be strait and ends must be open or use original bumper. Must have a 1 inch wide strap or no. 9 wire around bumper for saftey
6. No tires bigger than 15" 6 ply
7. No extra welds anywhere but front bumper and you may weld trans mount and engine mounts solid
8. **A simple home made shifter only if identical to a re manufactured shifter ... will not get in!**
9. Doors No. 9 wire only 2 strands per door.  
Tailgate 2 strands may wire to frame in 2 places.  
Hood 2 strands to frame or bumper in 2 places.
10. 4 frame patches 2 on each side front and back 4 x 4 patches
11. **No slider drive shafts**  
No steering replacements  
No pedal replacements  
No seam welding  
No modified engines or Tran  
No cradles  
No forklift tires
12. You may weld rear end  
No replacing rear end  
No reinforcing rear end
13. Ends of bumpers need to be open

**THIS IS IT - - - THIS IS ALL YOU CAN DO**

**No Exceptions on these Rules...**

**If it is in the rules DO IT – If not DON'T**

Check All Rules before Coming General Rules apply to all classes

Contact Stacey Holsapple @217-923-1507

or Dustin McCullough @ 217-251-4614