Winner - \$1000 Second Place - \$ 300

Third Place - \$200

- 1. Battery secured in floorboard and covered.
- 2. Gas can mounted in bed and covered.
- 3. Gas tank protector no farther back than 40" from bottom of front seat. May be 6" wider than gas can on each side not full width of truck.
- 4. Cage to body only= Dash Bar- Front driver and passenger door protectors and seat bar may have a rollover bar (only)
- 5. You may add a 4 x 4 bumper 1/25 inch thick must be strait and ends must be open or use original bumper. Must have a inch wids trap or no. 9 wire around bumper for saftey
- 6. No tires bigger than 15" 6 ply
- 7. No extra welds anywhere but front bumper and you may weld trans mount and engine mounts solid
- 8. A simple home made shifter only if identical to a re manufactured shifter ... will not get in!
- Doors No. 9 wire only 2 strands per door.
 Tailgate 2 strands may wire to frame in 2 places.
 Hood 2 strands to frame or bumper in 2 places.
- 10. No steering replacements
 - No pedal replacements No seam welding
 - No patches
 - No modified engines or Tran
 - No modified el
 - No cradles
 - No forklift tires
- 11. You may weld rear end No replacing rear end No reinforcing rear end

THIS IS IT - - - THIS IS ALL YOU CAN DO

No Exceptions on these Rules... If it is in the rules DO IT – If not DON'T

Check All Rules before Coming General Rules apply to all classes Contact Stacey Holsapple @217-923-1507

Scott Justice @ 217-251-6094 or Dustin McCullough @ 217-251-4614