



# DEMOLITION DERBY

CUMBERLAND COUNTY FAIRGROUNDS | 701 W CUMBERLAND • GREENUP, ILLINOIS

## SATURDAY, MAY 28TH, 2022

### STOCK COMPACT

**1st Place - \$5000**

**2nd Place - \$1000**

**3rd Place - \$500**

**Inspection 1:00 - 4:00 PM**

**Start Time: 6 PM**

**\$50 ENTRY FEE**

**\$40 PASSENGER**

**15 CARS PER HEAT | TOP 5 CARS OUT OF EACH HEAT WILL ADVANCE TO FEATURE**

1. 109" Wheelbase or Less.
2. All vehicles must be stock framed and bodied, but motor swaps are allowed no modified engines. 4- and 6-cylinder engines only. No extra reinforcements may be made to frames or bodies, no welds anywhere but front bumper and doors.
3. All doors are to be fastened shut by #9 wire, chain or weld.
4. Hoods need to be open for inspection. Hoods may be fastened shut in four (4) places total. Two (2) strands of #9 wire per hole, per location. You may wire around frames. Wiring to the front bumper in two (2) places only. Wiring may not be located behind radiator. No extra bolts in Hoods or Trunks. Trunk lids may be fastened shut using #9 wire or chain in no more than 4 places.
5. Any Factory Car bumpers and mountings are allowed. Weld your bumpers and mounts. No skid plates are allowed. Rear wheel drive cars bumper mounts must be on outside of frame and no direct welding bumper to frame must have mount. 4" x 12" Bumper Mount max. Bumper 3" from frame.
6. Front wheel drive cars only may add a 4 by 4 by quarter inch square bumper to the front and back no bumper skin needed. Front Bumper must be 3" from the frame – Rear Bumper may be welded to frame (NEED TO HAVE A SAFETY CHAIN WELDED OR BOLTED TO BUMPER THAT CONNECTS TO FRAME ON BOTH SIDES FOR SAFETY TO KEEP BUMPER FROM FLYING OFF) unless you use #9 wire in hood to bumper.
7. No Distributor protectors or engine cradles. Engine and transmission mounts maybe welded or chained. For safety, a driver's side and passenger bar, not to exceed 32" past the bottom rear of front seat and must be used. You may use spreader bars on both sides, but safety cages may only be fastened to sheet metal and may not be attached to the floor or frame of the vehicle with down bars. All gas tank protectors must stay in front of rear axle and not to exceed 40" past bottom rear of driver's seat. Dash, rear, and sidebars must be welded in or bolted.
8. Frame seams may not be welded on stock Class and inspection holes must remain open. 3-inch patch may be used on one side of frame, front, and back a total of 4 patches, there must be a bend or rust hole in frame in order to put a 3" plate on one side of frame. No adding anything to the inside of frames, (Concrete, Steel, Wood, etc.) Hump plates for rear frames will not be allowed in compact class.
9. Keep the height of the vehicle reasonable. This will be to judges' discretion. Cars must have bounce to them. You may chain rear ends or wire them in place.
10. Stock rear ends and axles only! Rear ends may be welded.
11. NO Slider Shaft's
12. NO Double Tires or flaps of any kind – NO Split Rims – NO Wheel Protectors – NO Solid Tires all tires must have air - NO forklift tires NO Tires larger than 15" ... or heavier than 6 ply. You may use tractor type tread tires.
13. NO V8 Engines
14. NO All Threads or Bolts in Hood or Trunk
15. NO Built Pointed Bumpers, NO replicate bumpers
16. NEED to have at least 14" x 14" hole in hood in case of fire.
17. NO aftermarket shifters
18. NO aftermarket foot-feets
19. You may replace steering columns
20. NO adding to struts but you may weld them.

**No Profanity on Any Cars!**

**No Exceptions on these Rules...If it is in the rules DO IT (if not DON'T)**

**Check All Rules before Coming. General Rules apply to all classes.**

**Contact Stacey Holsapple @ 217-923-1507 or Scott Justice @ 217-251-6094 or**

**Dustin McCullough @ 217-251-4614**