



# DEMOLITION DERBY

## # 3. Stock Mid-Size Cars

Saturday, September 29th, 2018 Cumberland Co. Fairgrounds Greenup

\$1000 Stock Class Winner • \$300 Second Place • \$200 Third Place

Sign-in opens at 4pm – Derby at 6:00 pm.

All entries must be on the grounds 1-hour prior to show!

**\$40 entry fee for Stock Class; \$25 entry fee for Passenger**

**The following are Stock Mid-Size Class rules.**

1. **112" or less wheel base**
2. All vehicles must be stock framed and bodied, but motor swaps are allowed. No extra reinforcements may be made to frames or bodies, and no welding seams or peep holes closed on frames.
3. All doors are to be fastened shut by #9 wire or chain. You may weld doors. No welding trunks in Stock Class. If wiring is used, **no more than two (2) strands of #9 wire may be used per hole**. Only one (1) run of chain per hole and must be fastened securely by welding of chain or bolting.
4. Front and rear hoods may be fastened shut in **six (6) places total**. Two (2) strands of #9 wire per hole, per location. You may wire around frames. Wiring to the front bumper in **two (2) places only**. Wiring may not be located in front of or behind radiator. Trunk lids and tailgates may be fastened shut using #9 wire or chain in no more than 6 places.
5. Any Factory Car bumpers and mountings are allowed. AU bumpers and mountings must look stock. Weld your bumpers and mounts. No skid plates are allowed. \*\*\* **Bumpers must have mounting brackets**. NO direct welds to frame. Rear wheel drive cars must have bumper mounts on outside of frame.
6. No Distributor protectors or engine cradles. Engine and transmission mounts may be welded or chained. For safety, a driver's side bar, not to **exceed 32" past bottom rear** of front seat. You may use spreader bars on both sides, but safety cages may only be fastened to sheet metal and may not be attached to the floor or frame of the vehicle with down bars. All cages not to exceed **32" past bottom rear of driver's seat**. Dash, rear, and sidebars must be welded in or bolted.
7. Frame seams may not be welded on stock Class and inspection holes must remain open. 3 inch patch may be used on one side of frame, front, and back a total of 4 patches. **If patches are added there must be a bend or rust spot in frame where patch is added**. No adding anything to the inside of frames, (Concrete, Steel, Wood, etc.) Hump plates for rear frames will not be allowed in stock class.
8. Keep the height of the vehicle reasonable. This will be to judges' discretion. Cars must have bounce to them. You may chain rear ends or wire them in place.
9. Stock rear ends and axles only! Rear ends may be welded, posi-traction, or stock,
10. **No tires larger than 15". Rims** must be free of wheel weights and **5 lugs**, No 6 or 8 lug rims. No split rims, and no studded tires. Water is allowed. \*\*\* **No solid tires must have air in all tires**.
11. Front wheel drive cars only may add a 4 by 4 by quarter inch square bumper to the front and back must have skin on it.
12. **NO Slider Shaft's**
13. **NO Double Tires**
14. **NO V8 Engines**
15. **ANY ADD ON STOCK BUPMER CANNOT BE MODIFIED IN ANY WAY!**

Check All Rules before Coming

General Rules apply to all classes

Contact Stacey Holsapple @ 217-923-1507 or  
Scott Justice @ 217-251-6094