

CENTRAL ILLINOIS CHAMPIONSHIP

LIMITED WELD FULL SIZE CARS CUMBERLAND COUNTY FAIRGROUNDS

October 7, 2023

Winner - \$1500 Second Place - \$300 Third Place - \$200

6 pm

1. No Imperials, Suicide door Lincolns, Hearses, 4x4 vehicles, or Convertibles will be allowed.
2. All vehicles must be stock framed and bodied, but motor swaps are allowed.
3. All doors are to be fastened shut by #9 wire, chained, or welded.
4. Hood may be fastened shut in six (^) places total. Two (2) strands of #9 wire per hole, per location. You may wire around frames. Wiring to the front bumper in tow (2) places only. 2- ¾ all thread one on each side and may go through the frame may be used on either side of the radiator support. Trunk lids may be fastened shut using #9 wire, chain, or weld, you may use 2 all thread 1 on each side ¾ inch, can go through the frame.
5. You may use or reinforce any original car bumper or you may use a replicate car bumper but it must stay within the factory specifications
6. For safety, a driver's side bar, not to exceed 40" past bottom***rear of driver's seat. You may use spreader bars on both sides, but safety cages may only be fastened to sheet metal and may not be attached to the floor or frame of the vehicle with down bars. All cages not to exceed 40" past bottom rear of driver's seat. Dash, rear, and sidebars must be welded in or bolted.
7. Frame seams may be welded, and inspection holes must remain open. There must be a bend or rusted frame in order to use a use a patch to frame. 6-inch patch may be used on one side of the frame, front, and back a total of 6 patches, 3 on each side. No adding anything to the inside of frames (Concrete, Steel, Wood, Etc.) Hump plates for rear frames will be allowed. 8" down from top of hump both sides of frame.
8. No Imperial sub-frames will be allowed. Keep the height of the vehicle reasonable. This will be to judges' discretion.
9. 3/4 ton rear ends may be used no bigger than 8 lug. Can change rear springs no more than 8 leaf springs per side. May be re enforced but no bracing to frame.
10. No tires larger than 16". Rims must be free of wheel weights. No split rims, and no studded tires. Water is allowed. No solid tires must have air.

11. NO Double Tires

YOU MAY:

- 1) Have slider shafts
- 2) Replace steering columns
- 3) Run 3 speed transmission
- 4) Bought shifters are allowed
- 5) Replace foot feeds
- 6) May have Lower Cradle
- 7) May Replace Body Bolts (maybe welded direct to frame.
- 8) No aftermarket ball joints or A-arms

No Exception on these on these No Rear End ProtectorsRules...

If it is in the rules DO IT – If not DON'T

Check All Rules before Coming General Rules apply to all classes

Contact Stacey Holsapple @217-923-1507

or Dustin McCullough @217-251-4614